



Compost Spreader

Shaktiman Compost Spreader is a simple, low cost and low maintenance machine. It does not only simplify the function of spreading compost but also ensures even quantity of compost spreading in each pass. Also, it is possible to preset the thickness layer of the compost spread which will not be affected by the driving speed of tractor. It is a multi-purpose- implement which is useful in spreading compost in farms, open field, green houses etc. The quick hitch frame of spreader makes it easier to hitch the spreader to tractor and also unhitching it from the tractor. This feature allows even a single operator to carry out the whole operation. Its thick body panels & axel and heavy duty bearings make the machine long lasting.



Advantages...

- It empowers the operator to easily adjust the width and thickness of the spread, which is not affected by the driving speed of tractor.
- Its adjustable spreading width allows the operator to spread the compost only where it is required, which helps in saving money on compost.
- It is a multi-purpose machine which can be used to spread gravel, sand, saw dust and such granule materials apart from compost.
- While operating, a thick rubber strip shoots out any non granule material; such as small rocks and stones; and thus dismisses the possibility of spreading of such particles with the actual material.
- It increases the fertility of soil by uniformly spreading the compost on the surface of the soil.
- The hydraulic drive of drum enables the operator to obtain a large range of thickness of compost layer.



Compost Spreader - Technical Specifications

SPECIFICATIONS	SHCS 1.5M	SHCS 1.8M
Working Width (mm / inch)	1500 / 59.05	1800 / 70.87
Tractor Power (HP / Kw)	35-45 / 26-34	40-50 / 30-37
Thickness of Compost Layer (mm / inch)	2-10 / 0.08-0.39	2-10 / 0.08-0.39
Loading Capacity (Kg / lbs)	750 / 1650	900 / 1980
Overall Width (mm / inch)	1730 / 68.11	1730 / 68.11
Overall Length (mm / inch)	2000 / 78.74	2300 / 90.55
Overall Height (mm / inch)	1300 / 51.18	1300 / 51.18
Three Point Hitch	Cat-II	Cat-II

The company reserves absolute rights to modify the specifications of machine and components therein without any prior notice.

Available Variants :

1. Mechanical Wheels



2. Hydraulic Motor Drive



Tirth Agro Technology Pvt. Ltd.

"SHAKTIMAN", Survey No.-108/1, Plot No. B, NH-27, Nr. Bharudi Toll Plaza, Bhunava (Village), Taluka: Gondal, Dist.: Rajkot. State: Gujarat- INDIA, Pin – 360311
 Phone: + 91 (2827) 661637 (30 Lines), + 91 (2827) 270537, Fax: + 91 (2827) 270457.
 Email: info@shaktimanagro.com, Web: www.shaktimanagro.com, CIN: U72900GJ2000PTC 038435
 Correspondence : Nr. Hotel Krishna Park, N.H. 27, Vavdi, Rajkot - 360 004, Gujarat, India.

